

The background is a solid teal color. On the left side, there are several large, overlapping, white, abstract shapes that resemble stylized letters or symbols, such as 'O', 'A', and 'E'. On the right side, there are several horizontal white bars of varying lengths, some with rounded ends, stacked vertically.

Technical Specs

FEATURES

- Cement-Acrylic Hybrid
- Withstands Wind-Driven Rain
- Water Vapor Permeability
- Long-Term Durability
- Extremely Low VOC
- Recoat in 1 hour
- Alkali Resistant
- Can fill and bridge cracks
- UV Resistance
- Textured Finish
- Applies to fresh concrete at 7 days

SPECIFICATION

Vehicle Type:	Cement-100% Acrylic
Finish:	Flat (gloss 1 to 3 at 60 degrees)
VOC Content:	<20 g/L
Solids by Volume:	56.14%
Weight per gallon:	10.93 lb./gal.
Coverage:	150 to 200 ft ² /gal. (2.45 to 3.93 m ² /L)*
Wet film coat:	4 mils to 6 mils
Dry film coat:	2 mils to 3 mils
Pot life:	7 hours**
Drying Time:	@ 75°F, 50% RH:
Touch:	20 minutes***
Recoat:	1 hour*

* Theoretical coverage is 320 ft²/gal. This figure does not include loss due to surface irregularities and porosity, or material loss due to application method or mixing. The reported coverage range is typical for porous substrates.

This product can be used for a one-coat application. For broad porous areas, a second coat may be required to achieve a uniform appearance and to ensure best performance.

** Temperature and relative humidity dependent

*** Note: Product variables include ambient temperature, surface temperature and use on vertical surfaces.



FLYING PIG
COATINGS

888.354.1118 ○ flyingpigcoatings.com